



VIMEK 606 TT



High ground clearness och low ground pressure for unique mobility. Extreme low fuel consumption and low investment costs for good total economy. Vimek 606 TT, an effective 6 WD forwarder and add our unique harvester Vimek 404 T and we offer you a complete machine group for no branch road thinning!



Technical specification Vimek 606 TT

Engine

Kubota D 902-E
18 kw/3.600 rpm

Speed

0-20 km/hour

Transmission

Variable mechanical

Generator

12 V, 60A

Front tires

405/70-24

Rear tires

400/60-15,5

Ground clearness

40 cm

Hydraulic

Flow 27 l/min 175 bar

Length

6,20 m, loading area 1,4 m²

Width

1,80 m

Loading capacity

3.000 kg

Weight incl. crane

2.960 kg

Crane

Mowi 2046
Max reach, 4,60 m
Lifting capacity at 4 m 440 kg
Gripping area, 0,16 m²
Turning angle, 250°
Rotator, continues rotation

Extra accessories

Wheel tracks
Diesel engine heating system
Wheel chains
Curtains for sun protection
Dolly trailer
Xenon lights
Radio controlled hydraulic winch
Bucket attachments
CD/Radio

VIMEK

For more information and to find your nearest retailer, please visit our website www.vimek.se/