



VIMEK 620 Minimaster



The 8-wheel driven mini-forwarder easy to maneuver thanks to servo steering function. Now with new accessories, wider tires and wheels tracks for the trailer. Ground clearance of almost 40 cm and a smooth underside which protects all the vulnerable parts all together offers unique mobility for heavy loads in difficult terrain. Vimek 620 Minimaster – for you different kind of needs!



Technical specification Vimek 620 Minimaster

Engine

Honda 620 cc
Generator, 20 A at 2200 rpm

Fuel tank

14 liters

Gear box

High, low, reverse

Transmission

Variable mechanical

Speed

0-28 km/hour

Tires

25 x 8,50 x 14
alt. 27 x 11 x14

Weight tractor

524 kg

Ground clearness

38 cm

Length

2,08 m

Width

1,15 m

Height

1,50 m

Servo steering

Hydraulic Orbitrol

Rear axle

Oscillation +/- 30°

Hydraulic

20 l/min 175 bar

Crane Vimek 362

Max reach, 3,60 m
Turning angle, 210°
Rotator, continues rotation
Gripping area, 0,15 m²
Weight incl. stabilizers and
protection guard, 341 kg

Driven trailer

Bogie oscillation, 25 cm
Capstan between wheels
Loading capacity, 2.000 kg
Loading area, 0,8 m²

Weight incl. crane and trailer

1.200 kg

Extra accessories

Wheel tracks
Snow blade
Wheel chains
Load holder for winch connection
Radio controlled hydraulic winch
Bucket attachments
Working lights installed on crane
Chain saw holder

VIMEK

For more information and to find
your nearest retailer, please visit our
website www.vimek.se