



Large and powerful forwarder with 50% more loading capacity compared with its predecessor Vimek 606TT and increased mobility with help from a complete new trailer design. Front end from Vimek 606 BioCombi, combined with new longer and stronger crane as well as improved environment for the driver. Low fuel consumption and low investment costs for good total economy. Vimek 608, an effective forwarder that together with harvester Vimek 404T3 forms the Dream Team for no branch road thinning.



Technical specification Vimek 608

Engine

Kubota D 902-E
18 kw/3.600 rpm

Speed

0-25 km/hour

Transmission

Variable mechanical

Generator

12 V, 60A

Front tires

405/70-24

Rear tires

400/60-15,5

Ground clearness

40 cm

Hydraulic

Flow 35 l/min 200 bar

Length

6,20 m, loading area 1,65 m²

Width

1,90 m

Loading capacity

4.500 kg

Weight incl. crane

3.500 kg

Crane

Mowi P25
Max reach, 5,2 m
Lifting capacity at 5,2 m 330 kg
Gripping area, 0,16 m²
Turning angle, 250°
Rotator, continues rotation

Extra accessories

Wheel tracks
Diesel engine heating system
Wheel chains
Curtains for sun protection
Dolly trailer
Xenon lights
Radio controlled hydraulic winch
Bucket attachments
CD/Radio
Grapple tilt
Swing damper
Crane damper for Lift and
Swing function

VIMEK

For more information and to find your nearest retailer, please visit our website www.vimek.se!